


SQUARE LED

CE IP20 150 355

15









JET.5290.157 3 LEDx1,2W/2,4W 350/700mA

Versione con LED tono bianco naturale 4000K, con lenti.
Version with LED natural white 4000K, with lenses.
Version avec LED blanc naturel 4000K, avec lentilles.


JET.5290.158 3 LEDx1,2W/2,4W 350/700mA

Versione con LED tono bianco caldo 3000K, con lenti.
Version with LED warm white 3000K, with lenses.
Version avec LED blanc chaud 3000K, avec lentilles.




Driver forniti su richiesta come accessori.
Drivers offered on demand as accessories.
Driver fournis séparément comme accessoires.

Accessori / Accessories / Accessoires




LAA.5100.006

Gruppo lenti per fascio medio 20°.
Group lens for medium beam 20°.
Groupe lentilles pour faisceau medium 20°.




LAA.5100.007

Gruppo lenti per fascio stretto 8°.
Group lens for narrow beam 8°.
Groupe lentilles pour faisceau 8°.




AAA.TRSL01

Driver per 1 apparecchio da 3 LED 350mA.
Driver for 1 fitting for 3 LED 350mA.
Driver pour 1 appareil de 3 LED 350mA.




AAA.TRSL31

Driver per 1 apparecchio da 3 LED 700mA.
Driver for 1 fitting for 3 LED 700mA.
Driver pour 1 appareil de 3 LED 700mA.



AAA.TRSL05

Driver per max 3 apparecchi da 3 LED 350mA.
Driver for max 3 3 LED fittings 350mA.
Driver pour max 3 appareils de 3 LED 350mA.



AAA.TRSL35

Driver per max 2 apparecchi da 3 LED 700mA.
Driver for max 2 3-LED fittings 700mA.
Driver pour max 2 appareils de 3 LED 700mA.