

ADAM 1R RD

design Ikaru Mori



FRAME

TRIMLESS

Apparecchio a incasso soffitto per l'illuminazione di spazi commerciali. Costruito in metallo verniciato a polvere, previo trattamento di protezione di fondo. L'apparecchio è dotato di un sistema che consente l'orientabilità delle ottiche oltre i 45° e un sistema telescopico per regolare la distanza dal soffitto. Disponibili due tipi di ottiche, a fascio medio e diffuso.

Recessed features designed for light commercial and residential spaces. Made of extruded, die-cast aluminium with powder-coated finish and under-layer protection. Adam 1R RD has an integrated telescoping system to adjust the distance from the ceiling and the inner portion can be oriented up to 45°. Different heights and various lighting beam are available.



FAMILY

www.lucitalia.it

ADAM 1R RD



www.lucitalia.it

159

ADAM 1R RD

incasso soffitto
ceiling recessed




Adam 1R RD versione ad incasso è dotata di un sistema telescopico. Sono disponibili due moduli versione 11 e versione 25. Il modulo 11 può essere installato arretrato di 1 cm e fino a 5 cm sporgente rispetto al soffitto. Il modulo 25 può essere installato sporgente rispetto al soffitto da 12,5 cm sino a 18,5 cm. Inoltre è possibile regolare l'ottica interna in 3 diverse posizioni: a filo estruso, arretrata di 1 cm ed arretrata di 3 cm per consentire un ottimale confort visivo.

Adam 1R RD recessed features an integrated telescoping system. 11cm and 25cm telescoping modules available. 11cm module can be fixed in positions within the fixture frame ranging from 1cm above the ceiling to 5cm below the ceiling. 25cm module can be fixed within the fixture frame in positions ranging from 12.5cm to 18.5cm below the ceiling. In addition, each module is flexible within itself. It can be positioned either flush with the module trim or recessed within itself 1cm or 3cm.




L'ottica ha una doppia orientabilità sino a 25°+25°. La peculiarità delle ottiche è Twist & Look (griglia e blocco). Si sostituiscono facilmente e consentono la massima flessibilità anche ad apparecchi montati.

Optics are adjustable on both axes up to 25°. Twist and look optics are installed in an instant without tools, are easily replaced and allow maximum flexibility in new and existing applications.



Adam R RD viene fornito con un riflettore standard a 60°. Su richiesta è disponibile un secondo riflettore di 26° (fascio medio).

Adam R RD comes with a standard 60° reflector. Upon request, a second 26° medium beam reflector is available.



Adam 1R RD 00 CR LED incasso soffitto / ceiling recessed



20351 10W 1 LED 3000K CRI > 85 60° 25°+25° 770 lm 220-240V 50/60 Hz alimentatore elettronico remoto incluso remote electronic driver included LED incluso LED included

Finiture / Finish > ☐ bianco opaco / matt white **20351.01**




20353 50W QR-CBC51 GU5.3 CRI > 90 12°/24°/38° 15°+15° 600 lm 12V alimentatore elettronico non incluso electronic driver not included ILCOS: HRG

Finiture / Finish > ☐ bianco opaco / matt white **20353.01** L'alimentatore deve essere ordinato separatamente / Electronic ballast must be ordered separately.




20354 50W PAR16 GU10 CRI > 95 8°/24°/38° 15°+15° 900 lm 220-240V 50/60 Hz tensione di rete mains voltage ILCOS: HEGPAR

Finiture / Finish > ☐ bianco opaco / matt white **20354.01**



20355 10W 1 LED 3000K CRI > 85 60° 25°+25° 800 lm 220-240V 50/60 Hz alimentatore elettronico remoto incluso remote electronic driver included LED incluso LED included

Finiture / Finish > ☐ bianco opaco / matt white **20355.01**



20357 50W QR-CBC51 GU5.3 CRI > 80 12°/24°/38° 15°+15° 800 lm 12V alimentatore elettronico non incluso electronic driver not included ILCOS: HRG

Finiture / Finish > ☐ bianco opaco / matt white **20357.01** L'alimentatore deve essere ordinato separatamente / Electronic ballast must be ordered separately.



20358 50W PAR14 GU10 CRI > 95 8°/24°/38° 15°+15° 900 lm 220-240V 50/60 Hz tensione di rete mains voltage ILCOS: HEGPAR

Finiture / Finish > ☐ bianco opaco / matt white **20358.01**




20359 10W 1 LED 3000K CRI > 85 60° 25°+25° 800 lm 220-240V 50/60 Hz alimentatore elettronico remoto incluso remote electronic driver included LED incluso LED included

Finiture / Finish > ☐ bianco opaco / matt white **20359.01**



20360 50W PAR14 GU10 CRI > 95 8°/24°/38° 15°+15° 900 lm 220-240V 50/60 Hz tensione di rete mains voltage ILCOS: HEGPAR

Finiture / Finish > ☐ bianco opaco / matt white **20360.01**



20361 10W 1 LED 3000K CRI > 85 60° 25°+25° 800 lm 220-240V 50/60 Hz alimentatore elettronico remoto incluso remote electronic driver included LED incluso LED included

Finiture / Finish > ☐ bianco opaco / matt white **20361.01**



20362 50W PAR14 GU10 CRI > 95 8°/24°/38° 15°+15° 900 lm 220-240V 50/60 Hz tensione di rete mains voltage ILCOS: HEGPAR

Finiture / Finish > ☐ bianco opaco / matt white **20362.01**

20363 10W 1 LED 3000K CRI > 85 60° 25°+25° 800 lm 220-240V 50/60 Hz alimentatore elettronico remoto incluso remote electronic driver included LED incluso LED included

Finiture / Finish > ☐ bianco opaco / matt white **20363.01**

20364 50W PAR14 GU10 CRI > 95 8°/24°/38° 15°+15° 900 lm 220-240V 50/60 Hz tensione di rete mains voltage ILCOS: HEGPAR

Finiture / Finish > ☐ bianco opaco / matt white **20364.01**

20365 10W 1 LED 3000K CRI > 85 60° 25°+25° 800 lm 220-240V 50/60 Hz alimentatore elettronico remoto incluso remote electronic driver included LED incluso LED included

Finiture / Finish > ☐ bianco opaco / matt white **20365.01**

20366 50W PAR14 GU10 CRI > 95 8°/24°/38° 15°+15° 900 lm 220-240V 50/60 Hz tensione di rete mains voltage ILCOS: HEGPAR

Finiture / Finish > ☐ bianco opaco / matt white **20366.01**

20367 10W 1 LED 3000K CRI > 85 60° 25°+25° 800 lm 220-240V 50/60 Hz alimentatore elettronico remoto incluso remote electronic driver included LED incluso LED included

Finiture / Finish > ☐ bianco opaco / matt white **20367.01**

20368 50W PAR14 GU10 CRI > 95 8°/24°/38° 15°+15° 900 lm 220-240V 50/60 Hz tensione di rete mains voltage ILCOS: HEGPAR

Finiture / Finish > ☐ bianco opaco / matt white **20368.01**

20369 10W 1 LED 3000K CRI > 85 60° 25°+25° 800 lm 220-240V 50/60 Hz alimentatore elettronico remoto incluso remote electronic driver included LED incluso LED included

Finiture / Finish > ☐ bianco opaco / matt white **20369.01**

20370 50W PAR14 GU10 CRI > 95 8°/24°/38° 15°+15° 900 lm 220-240V 50/60 Hz tensione di rete mains voltage ILCOS: HEGPAR

Finiture / Finish > ☐ bianco opaco / matt white **20370.01**

20371 10W 1 LED 3000K CRI > 85 60° 25°+25° 800 lm 220-240V 50/60 Hz alimentatore elettronico remoto incluso remote electronic driver included LED incluso LED included

Finiture / Finish > ☐ bianco opaco / matt white **20371.01**

20372 50W PAR14 GU10 CRI > 95 8°/24°/38° 15°+15° 900 lm 220-240V 50/60 Hz tensione di rete mains voltage ILCOS: HEGPAR

Finiture / Finish > ☐ bianco opaco / matt white **20372.01**

20373 10W 1 LED 3000K CRI > 85 60° 25°+25° 800 lm 220-240V 50/60 Hz alimentatore elettronico remoto incluso remote electronic driver included LED incluso LED included

Finiture / Finish > ☐ bianco opaco / matt white **20373.01**

20374 50W PAR14 GU10 CRI > 95 8°/24°/38° 15°+15° 900 lm 220-240V 50/60 Hz tensione di rete mains voltage ILCOS: HEGPAR

Finiture / Finish > ☐ bianco opaco / matt white **20374.01**

20375 10W 1 LED 3000K CRI > 85 60° 25°+25° 800 lm 220-240V 50/60 Hz alimentatore elettronico remoto incluso remote electronic driver included LED incluso LED included

Finiture / Finish > ☐ bianco opaco / matt white **20375.01**

20376 50W PAR14 GU10 CRI > 95 8°/24°/38° 15°+15° 900 lm 220-240V 50/60 Hz tensione di rete mains voltage ILCOS: HEGPAR

Finiture / Finish > ☐ bianco opaco / matt white **20376.01**

20377 10W 1 LED 3000K CRI > 85 60° 25°+25° 800 lm 220-240V 50/60 Hz alimentatore elettronico remoto incluso remote electronic driver included LED incluso LED included

Finiture / Finish > ☐ bianco opaco / matt white **20377.01**

20378 50W PAR14 GU10 CRI > 95 8°/24°/38° 15°+15° 900 lm 220-240V 50/60 Hz tensione di rete mains voltage ILCOS: HEGPAR

Finiture / Finish > ☐ bianco opaco / matt white **20378.01**

20379 10W 1 LED 3000K CRI > 85 60° 25°+25° 800 lm 220-240V 50/60 Hz alimentatore elettronico remoto incluso remote electronic driver included LED incluso LED included

Finiture / Finish > ☐ bianco opaco / matt white **20379.01**

20380 50W PAR14 GU10 CRI > 95 8°/24°/38° 15°+15° 900 lm 220-240V 50/60 Hz tensione di rete mains voltage ILCOS: HEGPAR

Finiture / Finish > ☐ bianco opaco / matt white **20380.01**

20381 10W 1 LED 3000K CRI > 85 60° 25°+25° 800 lm 220-240V 50/60 Hz alimentatore elettronico remoto incluso remote electronic driver included LED incluso LED included

Finiture / Finish > ☐ bianco opaco / matt white **20381.01**

20382 50W PAR14 GU10 CRI > 95 8°/24°/38° 15°+15° 900 lm 220-240V 50/60 Hz tensione di rete mains voltage ILCOS: HEGPAR</