

ZERO BLADE

design Francesco Brivio



FRAME



TRIMLESS

Incasto a parete a luce indiretta per creare effetti scenografici ed illuminare passaggi e corridoi. Corpo in pressofusione d'alluminio verniciato a polveri previo trattamento di fondo che garantisce una lunga protezione nel tempo. Parabola in alluminio purissimo (99.5%) ad emissione asimmetrica verso il basso. Funzionamento a tensione di rete con alimentatore elettronico incorporato, ove previsto.

Recessed Wall lamp with indirect light distribution creates scenic effects while lighting passageways and hallways. Body in cast aluminum finished in powder coat paint with under layer protection which guarantees protection over time. Super pure aluminum (99.5%) reflector emits indirect light downwards. Functions on main voltage, integral power supply included where needed.



FAMILY

LUCITALIA
MILANO

244

www.lucitalia.it



ZERO BLADE incasso parete / wall recessed

www.lucitalia.it

LUCITALIA
MILANO

245

ZERO BLADE incasso parete / wall recessed



La posizione arretrata del LED permette un buon comfort visivo. La luce direzionale asimmetrica non crea fastidio e genera luce soffusa d'ambiente.

Discreet LED placement provides visual comfort. Directional asymmetric light eliminates glare and provides soft diffused light.



La luce direzionale verso il basso di Zero Blade è ideale come segnapasso. L'altezza ideale di installazione è di 30/40cm dal pavimento. L'interdistanza fra un prodotto e l'altro è circa 2 mt.

Zero Blade is ideal for illuminating stairs, hallways and passageways. Ideal installation is 30/40cm (11.8"/15.75") above the floor.

LUCITALIA
MILANO


246

www.lucitalia.it

ZERO BLADE incasso parete / wall recessed

ZERO BLADE FRAME LED incasso parete / wall recessed

IP40 - Classe I / Class I - CE / F



Emissione asimmetrica / Asymmetric beam




21801 4W 1 LED 3000K CRI > 85  asimmetrico / asymmetric ottica fissa / fixed lens 400 lm 350 mA alimentatore elettronico incluso / electronic driver included  LED incluso / LED included

Finiture / Finish >  bianco opaco / matt white **21801.01**  grigio argento opaco / matt silver grey **21801.19**

ZERO BLADE GLASS FRAME LED incasso parete / wall recessed

IP40 - Classe I / Class I - CE / F



Emissione asimmetrica / Asymmetric beam




21806 4W 1 LED 3000K CRI > 85  asimmetrico / asymmetric ottica fissa / fixed lens 400 lm 350 mA alimentatore elettronico incluso / electronic driver included  LED incluso / LED included

Finiture / Finish >  vetro bianco / white glass **21806.01**  vetro nero / black glass **21806.22**

ZERO BLADE TRIMLESS LED incasso parete / wall recessed

IP40 - Classe III / Class III - CE / F



Emissione asimmetrica / Asymmetric beam



21802 4W 1 LED 3000K CRI > 85  asimmetrico / asymmetric ottica fissa / fixed lens 400 lm 350 mA alimentatore elettronico non incluso / electronic driver not included  LED incluso / LED included

Finiture / Finish >  bianco opaco / matt white **21802.01**  grigio argento opaco / matt silver grey **21802.19**

ACCESSORI / ACCESSORIES

22001 Alimentatore 15W 350mA IP20 solo per cod. **21402** (max 4 incassi) / 15W 350mA power supply unit IP20 only for cod. **21402** (max 4 pieces)



21804
Controcassa per muratura in cemento o laterizio
Concrete recessing box



21803
Controcassa per cartongesso (non obbligatoria)
Drywall recessing box (not mandatory)

Altri colori non standard sono disponibili con sovrapprezzo. / Other non-standard colors are available with surcharge.

A richiesta sono disponibili LED con temperature di colore diverse. / Upon request are available LED with different colours temperatures.

Legenda Simboli / Legend  Apertura del fascio luminoso / Beam width  Orientabile / Adjustable

www.lucitalia.it

LUCITALIA
MILANO

247