

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

PRODUCT DATA SHEET

Clivia

Code : 0710120B

PRODUCT FAMILY

Square applique for interior and exterior for wall or ceiling application (IP65).

MATERIAL CHARACTERISTICS

Body made from stabilized, anti-UV PC coloured granules white moulded white moulded

Reflector/ gear tray (FSD version) in stabilized anti-UV PC

Reflector (E27 version) in aluminium

White, convex diffuser in PMMA

Colours: White, Black

LIGHTING CHARACTERISTICS

High performance output due to internal reflector with mainly frontal and lateral light throw.

Lamp is in a fixed position

WIRING CHARACTERISTICS

Wiring on gear tray (FSD version only)

Wiring directly on base (E27 version only).

Ferromagnetic ballast

INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS

Fixture for direct wall/ ceiling fixing using n.3 screws and expansion caps (not supplied)

Rear cable entrance through cable tray or cable entrance through external canalisation max Ø20mm

Cable clamp for power supply cables 2x2.5mmq


Ordinary maintenance by loosening n.4 anti-drop screws holding diffuser for access to optic compartment

MEASUREMENT CHARACTERISTICS

Square fixture 300x300mm and a height of 110mm

Details

- Conformity with CEE directives
- Double insulation/class II
- Mounting on normal flammable surface
- Energy-saving fittings
- Resistant to atmospheric agents
- Shock-proof
- Inalterable to ultraviolet radiations
- IP 65



230V 50Hz FSD 2X18W 2G11							
CE							IP65

