

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

PRODUCT DATA SHEET

Pegaso

Code : CD040662

PRODUCT FAMILY

Large size round applique for interior and exterior for ceiling and semi-recessed on false ceiling application (IP55).

MATERIAL CHARACTERISTICS

Body and fixing ring diffuser made from Aluminium 99.9%, anodised, externally painted with acrylic bi-component metallized aluminium enamel, formulated in order to create a pleasing effect whilst achieving good mechanical and chemical strength (metallic grey colour), and internally painted with bi-component glossy white Acrylic enamel (modified thermo-setting acrylic resin-based), oven dried, giving good mechanical strength, and chemical and yellowing resistance (white colour)

Reflector/ Wiring covering made from thermoplastic

Transparent conical diffuser in PC internally prismatic

Brackets for semi-recessing made from galvanised sheet iron

Colour: Metallic Grey

LIGHTING CHARACTERISTICS

High performance output due to the coating and internal reflector with mainly frontal and lateral light throw (120°).

Lamp is in a fixed position

Lamp 100W FHD, 8800Lm, 3000°K, Ra 88 included (version FHD only)

WIRING CHARACTERISTICS

Wiring directly on base

Electronic ballast

INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS

Fixture for direct ceiling fixing using n.3 screws and expansion caps (not supplied)

Fixture for semi-recessing on false ceilings through a rear bracket on springs to loose from the inside

Rear cable entrance through cable tray

Cable clamp for power supply cables 3x2.5mmq

Ordinary maintenance by loosening n.6 anti-drop screws holding diffuser for access to optic compartment


MEASUREMENT CHARACTERISTICS

Circular fixture with a diameter of Ø600mm and a height of 136mm (ceiling application – Pegaso P)

Circular fixture with a diameter of Ø600mm and a height of 84mm, recessing hole Ø455mm (semi-recessed application – Pegaso I)

Details

- Conformity with CEE directives
- Mounting on normal flammable surface
- Energy-saving fittings
- Electronic supply
- Shock-proof
- IP 55



230V 50Hz FC 55W 2GX13

