

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l. The company reserves the right to change models, dimensions and materials at any time without notice.

PRODUCT DATA SHEET

Bambù wall with antiglare louver

Code : 0117108M

PRODUCT FAMILY

Outdoor residential round shaped complete with base for wall mounting (IP55) with antiglare accessory

MATERIAL CHARACTERISTICS

Body in galvanised steel with a thickness of 3mm

Degreasing, then phosphating with zinc salts followed by passivation with demineralized water and oven drying at 110°C

Thermosetting powder coating (based on carboxylated saturated polyester resins specifically selected for their high resistance to weathering) (hardener without TGIC) having pigments with high stability to light and heat

Thermopolymerization at 200°C

Diffuser, flush with body in transparent UV resistant, internally prismatic Polycarbonate, with antiglare accessory integrated, attached to the body through a bayonet connector and sealed with silicone gasket.

Antiglare accessory made in NYLON-FIBREGLASS30% painted with low gloss bi-component acrylic enamel, formulated with Acrylic-Isocyanate resins in order to achieve maximum strength and exceptional exterior hardness

Base in thermosetting resin (BMC), fixed internally to body of fitting

Colours: Metallic grey, Black

Screws in stainless steel A2

LIGHTING CHARACTERISTICS

Fluorescent light source, fixed position with antiglare accessory incorporated in the diffuser

WIRING CHARACTERISTICS

Lamp supplied with fitting

Ferromagnetic ballast

INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS

Base which allows fitting to be installed directly to wall with n.2 screws (NOT SUPPLIED), included in the base is also the gear tray.

Body fixed to base through 2 dissecting screws

Terminal for cables Ø2.5mm max

Ordinary maintenance carried out by removing diffuser by rotating and lifting, possible through bayonet connector


MEASUREMENT CHARACTERISTICS

Round shaped diffuser Ø78 with height 240mm, with integrated antiglare accessory Ø141

Round shaped body Ø76 curved at 90° with height 370mm (including diffuser)

Details

- Conformity with CEE directives
- Mounting on normal flammable surface
- Against lighting pollution
- Energy-saving fittings
- Resistant to atmospheric agents
- Shock-proof
- Fitting complete with lamp
- IP 55



230V 50Hz FSD 11W G23

