

Product Data Sheet

11906.01

Ugo LED

Ugo LED 12W

3000 K

medium beam emission (30°)

electronic driver included



01 ☐

Installation

For recessed installation in false ceiling.

Material

Frame and dissipater made of die-casting aluminium alloy.

Wiring housing made of black ABS materials to protect internal components.

Optical PMMA lens.

Mounting springs (for false ceiling up to 15 mm thickness) made of harmonic steel.

Wiring

Electronic driver 350mA, 220-240V 50/60 Hz included, to be connected to the fixture by quick connector.

Driver to install onto false ceiling structure next to the body fixture.

Compliance

Average luminance limits for DSE workstation

≥ 3000 cd/sqm at elevation angles $> 65^\circ$ (in accordance to EN 12464-1:2011)

UGR<19

Photobiological risk

Certified device in EXEMPT GROUP, in accordance with CEI EN 62471:2010.

IEC 598, CEI EN 60598-1 (CEI 34-21) CEI EN 62031 (34-118), CEI EN 62471 (76-9).

Luminous Fixture Flux ($T_a=25^\circ\text{C}$) = 1000 lm

Weight: 0.51 Kg

Supply Voltage: 220-240V 50/60 Hz

Total power: 14W

Power factor: 0.9

D: 138 mm

H1: 69 mm



N° Lamps: 1

Type: LED COB

Power: 12W

Color Temperature: 3000 K

Flow: 1250 lm ($T_c=25^\circ\text{C}$)

Tone: bianco / white

CRI: >80

Lamp included

