



## High-bay version

High-bay luminaires with steel structure include strong steel cables for quick adjustability which support one to four optical components. The 4-component type is available as a line or group with square frame. The family is completed by an aesthetically different offering: with central frame and four external optical elements.

## Light sources

The high-bay luminaires use very low voltage halogen lamps (75W max 12V G53), discharge lamps (35W - 70W GX8.5).



Base complete with ballast for high-bay luminaires.

High-bay luminaire for discharge lamps and very low voltage halogen lamps (12V).  
Structure in coated aluminium, adjustable optical assembly.  
Complete with electronic transformer.

# OCCHIO


DESIGN - **MARIANELLI - SORDINA**

CODE	DESCRIPTION
------	-------------



<b>3161</b>	MR (CDM-R111) - 70W - GX8.5 230V - 50Hz Colour: 01 - 02 - 18 IP 43 Kg 1.40
-------------	--






Size (mm)



<b>3261</b>	MR (CDM-R111) - 2 x 70W - GX8.5 230V - 50Hz Colour: 01 - 02 - 18 IP 43 Kg 2.20
-------------	--



<b>3361</b>	HMG (HALOSPOT111) MR (CDM-R111) - 70W - GX8.5 2 x 75W max - 12V - G53 230V - 50Hz Colour: 18 IP 40 Kg 3.50 Complete with ceiling rose and jack
-------------	---



## FIXING SYSTEM

Codes 3160, 3260, 3360, 3460, 3461, 3161, 3261, 3361 are provided with a jack for quick fixing.



01 white

02 black

18 grey

All luminaires include a jack for quick fixing. The optical housing can be adjusted separately on both axes.

**NOTE**