

DL 656 Remy

Lampada ad alogenuri metallici

Metal halide lamp



501.0656.1.86.00.1	HIT-CE	G12	1 x 70 W	BI/WH
501.0656.1.87.00.1	HIT-CE	G12	1 x 150 W	BI/WH


Ottica fascio medio 40°



501.0656.A.00.00.1 Ottica fascio stretto
20°



501.0656.A.00.00.2 Ottica fascio largo
50°



501.9510.A.01.0E.2 Alimentatore per
alogenuri metallici
1 x 70 W

ELETTRONICO



501.9510.A.02.0E.2 Alimentatore per
alogenuri metallici
1 x 150 W

ELETTRONICO




501.9510.A.01.00.2 Alimentatore per
alogenuri metallici
1 x 70 W



501.9510.A.02.00.2 Alimentatore per
alogenuri metallici
1 x 150 W



501.9501.A.00.CW.2 Cavo connessione con
presa



Cornice ed anello in alluminio
Scatola in metallo verniciato a polvere
Gruppo ottico orientabile ed estraibile
Staffe di fissaggio in acciaio zincato
Alimentatori e trasformatori non inclusi

Frame and ring in aluminium cast
Steel box powder coated
Adjustable and extractable optics
Fixing brackets in steel zinc.PI.

Colori disponibili : BI-bianco
Available color : WH-white
Lampade non incluse