

Lucio



Downlight

The downlights of serie "Lucio" is directed to compact fluorescent lamps; they are realized in thermoplastic material and they are available for many powers with metallized louvre, decorative glass diffuser or IP44 diffuser. Easy to install in any false ceiling with clamps, they are realized in class II. They are available with starter wiring or with electronic ballast (on request also in emergency).

Materials

Body for wiring in black polypropylene. Frame in white or grey polycarbonate. Reflector in silver metallized polycarbonate with fixing clamps. Fluorescent lamps are not included.

Wiring

Class II magnetic wiring 230V 50 Hz or electronic 220/240V 50/60 Hz for compact fluorescent

lamps, electrical components with ENEC approval. Socket terminal 2P+T (section max 2,5 mm²). In accordance with standard IEC 598, CEI EN 60598-1 (CEI 34-21), CEI EN 60598-2-2 (CEI 34-31). Emergency wiring in accordance with standard CEI EN 60598-2-22 (CEI 34-22) with an emergency external kit (class II, IP40).



Lucio

A6833BI



Lamps not included

Code	Lamps Watt		magnetic wiring
A6833 BI-GR	1x26	FSQ G24d3	
A6843 BI-GR	2x26		
A6835 BI-GR	1x18	FSQ G24d2	
A6845 BI-GR	2x18		

Code	Lamps Watt		electronic wiring
EL6831 BI-GR	1x42	FSM Gx24q4	
EL6841 BI-GR	2x42		
EL6833 BI-GR	1x26	FSQ G24d3	
EL6843 BI-GR	2x26		
EL6835 BI-GR	1x18	FSQ G24d2	
EL6845 BI-GR	2x18		




pag. 358-359

Downlight for compact fluorescent lamps, direct light.

Wiring on request











- _____/E one lamp emergency continuous light with electronic ballast
- ED____ 220-240V 50-60Hz electronic dimmable ballast (see price list page 4)
- ED____/E one lamp emergency continuous light with dimmable ballast (see price list page 4)



Colours

BI

GR

 <div data-bbox="628 533 675 566">IP44</div>		<p>Code</p> <hr/> <p>4413016</p> <p>Transparent plastic cover for degree protection IP44.</p>
 <div data-bbox="628 880 675 913">IP44</div>		<p>Code</p> <hr/> <p>4413017</p> <p>Snap-in frosted cover for degree protection IP44.</p>
 <div data-bbox="628 1227 675 1261">IP20</div>		<p>Code</p> <hr/> <p>4413018</p> <p>Snap-in turbo raster metalized louvre.</p>
 <div data-bbox="628 1574 675 1608">IP20</div>		<p>Code</p> <hr/> <p>4413010</p> <p>Decorative frosted glass with transparent ring.</p>
 <div data-bbox="628 1921 675 1955">IP20</div>		<p>Code</p> <hr/> <p>4413011</p> <p>Decorative frosted glass.</p>