

Quadrato



Recessed spot quadrato

"QUADRATO": great functionality and essentiality in lighting with fluorescent spots for recessed mounting.

Available with glazed and lucid diffuser.

Magnetic or electronic ballast for compact fluorescent lamps 18w or 26w. It's dimensions allow an easy mounting in dropceilings with a limited height.



Quadrato

A6823SAGR



Code	Lamps Watt		magnetic wiring
------	---------------	--	-----------------

A6823SA BI•GR	2x26	FSQ G24d3	
---------------	------	--------------	--

A6825SA BI•GR	2x18	FSQ G24d2	
---------------	------	--------------	--

Code	Lamps Watt		electronic wiring
------	---------------	--	-------------------

EL6823SA BI•GR	2x26	FSQ G24q3	
----------------	------	--------------	--

EL6825SA BI•GR	2x18	FSQ G24q2	
----------------	------	--------------	--

Code	Lamps Watt		emergency electronic wiring
------	---------------	--	-----------------------------

EL6823/ESA BI•GR	2x26	FSQ G24q3	
------------------	------	--------------	--

EL6825/ESA BI•GR	2x18	FSQ G24q2	
------------------	------	--------------	--

Code	Lamps Watt		magnetic wiring
------	---------------	--	-----------------

A6829SA BI•GR	1x70	MD RX7s	
---------------	------	------------	--



pag. 357

Recessed light fitting for compact fluorescent or metal halide lamps, glazed diffuser



Body in white or grey zinc coated steel, provided with accessories for dropceilings.

Diffuser in glazed and lucid tempered glass.

Wiring: magnetic 230V-50Hz or electronic 220/240V-50/60Hz, electrical components with ENEC approval. Rigid cable H05V2-U section 0,75 mm² (CEI 20-20). Socket

terminal 2P+T (section max 2,5 mm²). In accordance with standard IEC 598, CEI EN 60598-1 (CEI 34-21), CEI EN 60598-2-2 (CEI 34-31).

Emergency wiring in accordance with standard CEI EN 60598-2-22 (CEI 34-22).



Colours

BI

GR

