

Designing light for exhibition and retail areas does not mean you have to forego creating evocative settings and arresting atmospheres.

The Run projector combines excellent lighting performance with great reliability and flexibility of use. This compact-sized luminaire is characterised by full adjustability as it can rotate both on the vertical and on the horizontal axis, enabling a accurately aimed light beam.

Characterised by a simple and elegant line, the Run projector has been designed mainly for installation on an electrical track.

Using a small accessory, it can however be installed either directly on the ceiling or in false ceilings.

Technical specifications

The luminaire is made of drawn aluminium with UV-stabilised epoxy polyester coat finish. Three different types of finishing are available: grey, white and black. It can be installed on the ceiling or in false ceiling through the special base, which can be used as a mechanical hook and as an electrical connection.

Structural features

Installation: track, ceiling, and false ceiling

Luminaire housing: extruded aluminium with coat finish

Light sources: discharge lamps, very low voltage halogen lamps 12V

Standard finishing: white, grey, black

IP 40 protection class

Insulation class: I 

Power supply: 230V-50Hz

Optical components and light sources

The adjustable optical component has been designed for use with 20W discharge lamp and 50W halogen lamps.

DISCHARGE LAMPS



MR - GX10	20W
MR - GX10	35W

VERY LOW VOLTAGE HALOGEN LAMPS (12V)















HRGI - GU5.3	max 50W
--------------	---------




Adjustable projector for discharge lamps, very low voltage halogen lamps (12V).
Equipped with electronic ballast.

RUN

DESIGN - QUATTROBI TECHNICAL DEPARTMENT


CODE	DESCRIPTION	
5500	MR (CDM-R) - 35W - GX10 230V - 50 Hz Colour: 01 - 02 - 18 IP 40 Kg 0.90	   
5501	MR (CDM-R) - 20W - GX10 230V - 50 Hz Colour: 01 - 02 - 18 IP 40 Kg 0.90	   
5502	HRGI - max 50W - 12V - GU5.3 230V - 50 Hz Colour: 01 - 02 - 18 IP 40 Kg 0.90	   




Size (mm)

ACCESSORIES


- 658 Adapter kit for ceiling installation (available colours: 01 - 02 - 18)
659 Adapter kit for recessed adapter - \varnothing 105 (available colours: 01 - 02 - 18)



658



659



\varnothing 105

01 white
02 black
18 grey

NOTE

