


Gypsum


Plaster recessed lighting fixture with fixed optical compartment. Dichroic or LED light source.

Empotrable de yeso con vano óptico fijo. Fuente luminosa dicróica o LED.

Встраиваемый гипсовый светильник с фиксированным отсеком для оптики. Источник света дихроичный или светодиодный.



finish	code	lamp	light source	H mm	LED colour	lm	Kg	m²	
E1	61450	LED	7,3W LED Array	101	N	900	1,52	0,004	III
E1	61450W	LED	7,3W LED Array	101	W	860	1,52	0,004	III




finish	code	lamp	bulb holder	H mm	Kg	m ³	
 E1	61430		QPAR16 GU10 max 35W - 240V	122/156	1,32	0,004	
 E1	61440		QR-CBC 51 GU5.3 max 35W - 12V	106	1,29	0,004	
				 126x126		 850	



DRIVER

62423 8W 200mA 40V (LED)



TRANSFORMER

57350 1 - 70W 12V (HALO)
1 - 50W 12V (LED)

53510 20 - 105W 12V

ACCESSORIES



60840 (art. 61430 - 61440)
Sandblasted glass.
Vidrio arenado.
Стекло пескоструйной обработки.



60830
Shim kit for installation on 12,5mm thick plasterboard.
Kit de espesores para instalación en cartón yeso de 12,5 mm de grosor.
Набор прокладок для установки в гипсокартоне толщиной 12,5 мм.